

KOHLER®

Roughing-In

K-792-H2, K-792-N1 STEEPING™ BATH BATH WHIRLPOOL

Product Information

With neck jets	K-792-N1	shown
Without neck jets	K-792-H2	not shown

Required accessories:	
Jet trim kit	K-9696
Grip rails (pair)	K-9623

Fixture*:	Basin area	Top area	Weight
Bathing well	43" (109.2 cm) x 19" (48.3 cm)	54" (137.2 cm) x 30" (61 cm)	420 lbs (190.5 kg)

Water depth (to overflow)	Capacity (to overflow)
15" (38.1 cm)	62 gal. (234.7 L)

* Approximate measurements for comparison only.

Product	Pump	Heater	V	A*
Neckjets	2 hp	1.5 kW	240	15
Without neckjets	1.5 hp	1.5 kW	240	11

* Approximate measurements for comparison only.

Drop-in cut-out	58-1/2" (148.6 cm) x 34-1/2" (87.6 cm)
Cut-out for undermount	K-584 template
Minimum access panel (required):	
Pump/control	34" (86.4 cm) W x 15" (38.1 cm) H

Required Electrical Service

Dedicated circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI) or Earth-Leakage Circuit-Breaker (ELCB):	
Pump/control	208-240 V, 20 A, 50/60 Hz

Installation Notes

Install this product according to the installation guide.

Floor support under whirlpool must provide for a minimum of 1500 lbs (680.4 kg) loading.

Cast iron whirlpools are extremely heavy, making some drop-in installations difficult. Splitting the deck/surround is recommended if installing into a deck.

Fixture conforms to ASME Standard A112.19.1M. All dimensions are nominal.

No change in measurements if connected with drain illustrated. (K-7161-AF or K-7161M-AF)

K-792-N1

